



99105-80000
4" tachometer / without monitor



99105-80002
4" speedometer



99105-80001
4" tachometer / monitor

4" tachometer

7,000 max R.P.M. Tachs are available with or without 4-Stroke monitor functions. Monitor functions include: Low Oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Rev Limit Warning.

99105-80000	Black – Without monitor functions
99105-80001	Black – With monitor functions

4" speedometer

Easy to read 4" Speedometer features include lighted dial, contoured pointer and fog resistant glass lens. *Requires Tubing 99105-80009.

99105-80002	Black 60 mph
99105-80009*	Speedometer Tubing

Economically priced, high quality instruments feature easy plug-in wiring connections, perimeter-lighted dial, black bezels, contoured pointers and fog resistant glass lenses. All use standard 2" or 4" diameters for easy dash installation.



99105-80003
2" fuel gauge



99105-80005
2" trim gauge



99105-80006
2" voltmeter



99105-80007
2" hour meter



99105-80008
2" engine monitor gauge



99105-80004
2" water pressure gauge

2" fuel Gauge

Adding a Fuel Gauge can help you monitor fuel level. Connects easily using your boat's fuel sending unit harness.

99105-80003 Black

2" hour meter

Handy Hour Meter helps you keep track of the time between services and total running time.

99105-80007 Black

2" trim gauge

To help maintain steering stability and good performance, proper trim angle is essential. The Trim Gauge helps you monitor the trim angle. For use with 2-wire senders.

99105-80005 Black

2" engine monitor gauge

Engine Monitor Gauge for 4-stroke engines helps alert you to low oil pressure, high engine temperature and engine over-rev.

99105-80008 Black

2" voltmeter

A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

99105-80006 Black

2" water pressure gauge 30psi

Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model.

99105-80004 Black

water pressure gauge installation kits

Kit includes fittings and hoses needed for motor to gauge connection.

34660-93J00 DF200/225/250

34660-96J00 DF150/175

34660-90J01 DF90/115/140

34660-90J01 DF60A/70A/80A/90A

34660-99E00 DF60/70

34660-90J01 DF40A/50A/60A

34660-87J00 DF40/50

SUZUKI

instruments



99105-80100
4" tachometer / without monitor



99105-80102
4" speedometer



99105-80101
4" tachometer / monitor

4" tachometer

7,000 max R.P.M. Tachs are available with or without 4-Stroke monitor functions. Monitor functions include: Low Oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Rev Limit Warning.

99105-80100	White – Without monitor functions
99105-80101	White – With monitor functions

4" speedometer

Easy to read 4" Speedometer features include lighted dial, contoured pointer and fog resistant glass lens. *Requires Tubing 99105-80009.

99105-80102	White 60 mph
99105-80009*	Speedometer Tubing

Economically priced, high quality instruments feature easy plug-in wiring connections, perimeter-lighted dial, polished stainless steel bezels, contoured pointers and fog resistant glass lenses. All use standard 2" or 4" diameters for easy dash installation.



99105-80103
2" fuel gauge



99105-80105
2" trim gauge



99105-80106
2" voltmeter



99105-80107
2" hour meter



99105-80108
2" engine monitor gauge



99105-80104
2" water pressure gauge

2" fuel Gauge

Adding a Fuel Gauge can help you monitor fuel level. Connects easily using your boat's fuel sending unit harness.

99105-80103 White

2" hour meter

Handy Hour Meter helps you keep track of the time between services and total running time.

99105-80107 White

2" trim gauge

To help maintain steering stability and good performance, proper trim angle is essential. The Trim Gauge helps you monitor the trim angle. For use with 2-wire senders.

99105-80105 White

2" engine monitor gauge

Engine Monitor Gauge for 4-stroke engines helps alert you to low oil pressure, high engine temperature and engine over-rev.

99105-80108 White

2" voltmeter

A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

99105-80106 White

2" water pressure gauge 30psi

Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model.

99105-80104 White

water pressure gauge installation kits

Kit includes fittings and hoses needed for motor to gauge connection.

34660-93J00 DF200/225/250

34660-96J00 DF150/175

34660-90J01 DF90/115/140

34660-90J01 DF60A/70A/80A/90A

34660-99E00 DF60/70

34660-90J01 DF40A/50A/60A

34660-87J00 DF40/50



34200-93J00
4" tachometer / monitor



34200-93J20
4" tachometer / without monitor



34200-93J40
4" tach / suzuki troll mode scale



37860-87L00
trolling mode control switch

4" tachometers

7,000 max R.P.M. Tachs are available with or without 4-Stroke monitor functions. Monitor functions include: Low Oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Rev Limit Warning.

34200-93J20	without monitor
34200-93J00	with monitor functions

trolling mode control switch

Allows the use of the Suzuki Troll Mode on equipped engines. When Troll mode is engaged, this switch allows for adjustments of engine RPM in 50 RPM increments, from idle to 1200 RPM to make setting and maintaining a trolling speed easy. Consult owners' manual or Suzuki Outboard Dealer for additional details on Suzuki Troll System operation.

37860-87L00	trolling switch
-------------	-----------------

4" tachometer with suzuki troll mode scale

Easy to read 4" Tachometer has a scale from 0-7,000rpms for standard use, and a secondary scale from 0-3,000rpms with markers at 50rpm intervals for use with the Suzuki Troll Mode System*. Gauge also includes warning lamps for Engine Temperature, Low Oil, Check Engine and Over-Rev. When in troll mode, Over-Rev lamp stays on to indicate that Troll mode has been engaged. The secondary RPM scale is designed to make setting and maintaining a lower troll speed simple. Fits DF 40A 50A 60A 70A 90A and DF300 (DF 300 requires SMIS gauges).

*See engine owners' manual for information about Suzuki Troll Mode system. Not all models come equipped with trolling mode system. Accessory Troll Mode Switch required for Suzuki Troll Mode System use. Suzuki recommends the use of this gauge for trolling use.

34200-93J40	DF40A/50A/60A/70A/80A/90A DF300 with SMIS gauges
-------------	---

Geunine Suzuki Instruments are custom-designed to provide the quality, reliability and value you expect from Suzuki Products. The wide selection allows you to accurately monitor a variety of essential functions. All instruments are lighted for night time boating and feature standard 2" and 4" diameters for easy installation.



34100-93J00
4" speedometer



34800-93J00
2" trim meter



34600-93J00
2" voltmeter



34300-93J00
2" fuel gauge



34500-93J00
2" hour meter



34650-93J20
2" water pressure gauge

4" speedometers

Bourdon-tube type speedometer with readings in M.P.H. and Km/h. Includes vinyl tube, plus all installation instructions and hardware. *Pitot tube 34190-87D00 must be ordered separately for DF50 and under models.

34100-93J00	80 mph
34100-93J20	50 mph (not shown)
34190-87D00*	Pitot Tube (not shown)

2" fuel gauge

Operates on 12 volts with magnetically damped needle. Works with most fuel tank sending units.

34300-93J00	Black
-------------	-------

2" hour meter

12 volt electric motor driven meter indicates the number of hours your outboard motor has been operated to indicate when periodic services are necessary.

34500-93J00	Black
-------------	-------

2" trim meter

Magnetic type gauge shows trim angle for optimum performance and efficiency.

34800-93J00	Black
-------------	-------

2" voltmeter

A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

34600-93J00	Black
-------------	-------

2" water pressure gauge 15psi

Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model.

34650-93J20	Black
-------------	-------

water pressure gauge installation kits

Kit includes fittings and hoses needed for motor to gauge connection.

34660-93J00	DF200/225/250
34660-96J00	DF150/175
34660-90J01	DF90/115/140
34660-90J01	DF60A/70A/80A/90A
34660-99E00	DF60/70
34660-87J00	DF40/50



34200-93J11
4" tachometer / monitor



34200-93J31
4" tachometer / without monitor



34200-93J50
4" tach / suzuki troll mode scale



37860-87L00
trolling mode control switch

4" tachometer with suzuki troll mode scale

Easy to read 4" Tachometer has a scale from 0-7,000rpms for standard use, and a secondary scale from 0-3,000rpms with markers at 50rpm intervals for use with the Suzuki Troll Mode System*. Gauge also includes warning lamps for Engine Temperature, Low Oil, Check Engine and Over-Rev. When in troll mode, Over-Rev lamp stays on to indicate that Troll mode has been engaged. The secondary RPM scale is designed to make setting and maintaining a lower troll speed simple. Fits DF 40A 50A 60A 70A 90A and DF300 (DF 300 requires SMIS gauges).

*See engine owners' manual for information about Suzuki Troll Mode system. Not all models come equipped with trolling mode system. Accessory Troll Mode Switch required for Suzuki Troll Mode System use. Suzuki recommends the use of this gauge for trolling use.

34200-93J50 DF40A/50A/60A/70A/80A/90A DF300 with SMIS gauges

trolling mode control switch

Allows the use of the Suzuki Troll Mode on equipped engines. When Troll mode is engaged, this switch allows for adjustments of engine RPM in 50 RPM increments, from idle to 1200 RPM to make setting and maintaining a trolling speed easy. Consult owners' manual or Suzuki Outboard Dealer for additional details on Suzuki Troll System operation.

37860-87L00 trolling switch

4" tachometers

7,000 max R.P.M. Tachs are available with or without 4-Stroke monitor functions. Monitor functions include: Low Oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Rev Limit Warning.

34200-93J31 without monitor
34200-93J11 with monitor functions

Geunine Suzuki Instruments are custom-designed to provide the quality, reliability and value you expect from Suzuki Products. The wide selection allows you to accurately monitor a variety of essential functions. All instruments are lighted for night time boating and feature standard 2" and 4" diameters for easy installation.



34100-93J11
4" speedometer



34800-93J11
2" trim meter



34600-93J11
2" voltmeter



34300-93J11
2" fuel gauge



34500-93J11
2" hour meter



34650-93J31
2" water pressure gauge

4" speedometers

Bourdon-tube type speedometer with readings in M.P.H. and Km/h. Includes vinyl tube, plus all installation instructions and hardware. *Pitot tube 34190-87D00 must be ordered separately for DF50 and under models.

34100-93J11	80 mph
34100-93J31	50 mph (not shown)
34190-87D00*	Pitot Tube (not shown)

2" fuel gauge

Operates on 12 volts with magnetically damped needle. Works with most fuel tank sending units.

34300-93J11	White
-------------	-------

2" hour meter

12 volt electric motor driven meter indicates the number of hours your outboard motor has been operated to indicate when periodic services are necessary.

34500-93J11	White
-------------	-------

2" trim meter

Magnetic type gauge shows trim angle for optimum performance and efficiency.

34800-93J11	White
-------------	-------

2" voltmeter

A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

34600-93J11	White
-------------	-------

2" water pressure gauge 15psi

Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model.

34650-93J31	White
-------------	-------

water pressure gauge installation kits

Kit includes fittings and hoses needed for motor to gauge connection.

34660-93J00	DF200/225/250
34660-96J00	DF150/175
34660-90J01	DF90/115/140
34660-90J01	DF60A/70A/80A/90A
34660-99E00	DF60/70
34660-87J00	DF40/50